



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁵ : A61M 29/02.	A1	(11) International Publication Number: WO 93/05842
		(43) International Publication Date: 1 April 1993 (01.04.93)

(21) International Application Number: PCT/US92/07948

(22) International Filing Date: 23 September 1992 (23.09.92)

(30) Priority data:
765,848 26 September 1991 (26.09.91) US

(71) Applicant: MEDTRONIC, INC. [US/US]; 7000 Central Avenue N.E., Minneapolis, MN 55432 (US).


(72) Inventors: SHIN, Don, Ik ; 12518 Glenoak Road, Poway, CA 92064 (US). ROUCHER, Leo, R., Jr. ; 1272 Simeon Place, Escondido, CA 92029 (US).

(74) Agents: SCHULTZ, Sandra, S. et al.; Medtronic, Inc., 7000 Central Avenue N.E., Minneapolis, MN 55432 (US).

(81) Designated States: CA, JP, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, SE).

Published*With international search report.**Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.*

(54) Title: CATHETER WITH SPRING COIL INNER LUMEN



(57) Abstract

An over-the-wire dilatation catheter with a spring coil inner lumen is disclosed. The wound wire of the spring coil inner lumen is preferably stainless steel flat wire, and the preferred dimensions for the flat wire are 0.0015 inch by 0.006 inch. Usually the inner lumen is jacketed with a biocompatible polymer, preferably polyethylene, and it may be enhanced by a lubricious coating on the interior. The outer shaft is preferably comprised of a stiffer proximal and a more flexible, narrower distal portion.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	FI	Finland	MN	Mongolia
AU	Australia	FR	France	MR	Mauritania
BB	Barbados	GA	Gabon	MW	Malawi
BE	Belgium	GB	United Kingdom	NL	Netherlands
BF	Burkina Faso	GN	Guinea	NO	Norway
BG	Bulgaria	GR	Greece	NZ	New Zealand
BJ	Benin	HU	Hungary	PL	Poland
BR	Brazil	IE	Ireland	PT	Portugal
CA	Canada	IT	Italy	RO	Romania
CF	Central African Republic	JP	Japan	RU	Russian Federation
CG	Congo	KP	Democratic People's Republic of Korea	SD	Sudan
CH	Switzerland	KR	Republic of Korea	SE	Sweden
CI	Côte d'Ivoire	LI	Liechtenstein	SK	Slovak Republic
CM	Cameroon	LK	Sri Lanka	SN	Senegal
CS	Czechoslovakia	LU	Luxembourg	SU	Soviet Union
CZ	Czech Republic	MC	Monaco	TD	Chad
DE	Germany	MG	Madagascar	TG	Togo
DK	Denmark	MI	Mali	UA	Ukraine
ES	Spain			US	United States of America

CATHETER WITH SPRING COIL INNER LUMEN
BACKGROUND OF THE INVENTION

Field of the Invention:

5 This invention relates to catheters for coronary angioplasty, particularly over-the-wire dilatation catheters.

Description of the Prior Art:

10 Catheters are tube-like members that are inserted into the body for various medical reasons, some diagnostic and others therapeutic. In general, catheters used for coronary angioplasty have an outer tube or shaft with a balloon near the distal tip. The catheter is threaded into the vasculature, with the balloon located within the stenosis. The balloon is then inflated to redistribute the plaque of the stenosis along the artery wall so that it does not block the
15 artery.

In some catheters, an attached stiffening wire extends through the shaft to the tip to aid in the insertion of the catheter into the arteries, which are twisted and tortuous. In some catheters, a separate inner tube, or lumen, extends within the
20 outer tube to hold the guidewire. Where the catheter is a fixed-wire catheter, the guidewire is fixed in place within the inner tube; when the catheter is an over-the-wire catheter, the guidewire is a separate unit which extends through the inner tube and out the open far end.

25 Among the considerations in designing the catheter is the axial strength of the system. The catheter must be sufficiently strong so that pushing the catheter at the user's end results in forward motion at the distal end. Where the catheter has an inner tube or lumen, it must be strong enough
30 to avoid collapse when the catheter extends around a corner.

Some catheters use metal in some locations in the catheter. In Kraus, et al., EPO published application 397,055, published November 14, 1990, the proximal end of the catheter shaft is formed of stainless steel, and a stainless steel coil forms the distal tip of the catheter beyond the balloon. A tip coil is also provided in Mar, U.S. Patent No. 4,771,778, issued September 20, 1988. In Schulte, U.S. Patent No. 3,738,365 issued on June 12, 1973, a small part of what is essentially the outer lumen of a drainage catheter is made extensible by including a metal coil.

In Sheldon, U.S. Patent No. 3,060,972, a flexible tube structure for an endoscopic device is formed of a plurality of end-to-end tubular units. In Bundy, et al., U.S. Patent No. 4,653,496, a helically wound coil having a concentric outer radial cutting cannula is disclosed for the removal of stenotic and occlusive lesions from the vascular system. In Goldberg, et al., U.S. Patent No. 4,351,341, issued September 28, 1982, Samson, et al., EPO publication 356,748 and Bazell, et al., U.S. Patent No. 4,444,188, issued April 24, 1984, the outer lumen of a balloon catheter includes a coil; the same is the case in Sharrock, U.S. Patent No. 4,368,730, issued January 18, 1983, which discloses a catheter-like introducer.

In Machold, et al., EPO publication 297,959 published August 31, 1988, the proximal end of the inner tube of a dilatation catheter has a stainless steel liner. In Pinchuk, et al., U.S. Patent No. 4,946,466, a balloon is affixed to a metallic, hollow guidewire.

In Dick, EPO published application 388,486, published September 26, 1990, a dilatation catheter has a regulating expanding device embodied in a connector having an "interlumen" made of a tightly wound polymer-coated metal coil.

In Buchbinder, et al., U.S. Patent No. 4,723,936, issued February 9, 1988, and owned by the assignee of the present invention, a catheter, fixed-wire, is disclosed which has an inner tube formed of coiled stainless steel flat wire.

5 In Hess, U.S Patent No. 4,808,164, issued February 28, 1989, and No. 4,927,413, issued May 22, 1990, a generally fixed-wire catheter is disclosed. The inner lumen is formed of a suitable metal and has an outside diameter of about 0.014 to 10 0.035 inches. A core is movably and removably mounted inside the lumen. A small "guidewire" extends from the distal tip of the catheter in some embodiments. In others, it extends from the distal tip of the core. Because the Hess catheters are essentially fixed-wire systems, with a core designed 15 particularly to fit the inner lumen, they are not available for use and insertion over a standard guidewire.

This can be a disadvantage of the Hess device. The core designed to go with the catheter must be used in most cases, and the catheter cannot be used in a system in which a small 20 guidewire needs to be carefully steered through a tortuous pathway ahead of the lesion, and the catheter then moved over the guidewire into place. What is apparently coils of round wire shown in the Hess device and a standard guidewire may easily lockup around corners if used together because the 25 standard wire also has a round coil. Finally, because the device appears to use a round coil, it lacks the axial strength and "pushability" which is needed in an over-the-wire catheter which does not have the added stiffening of a fixed wire.

30 The above description of art is not intended to constitute an admission that any patent, publication or other information referred to is "prior art" or is enabling with respect to this invention, unless specifically designated as such. In

addition, this section should not be construed to mean that a search has been made or that no other pertinent information as defined in 37 C.F.R. § 1.56(a) exists.

SUMMARY OF THE INVENTION

5 The invention in one aspect is an over-the-wire catheter with a spring coil inner lumen which avoids problems associated with the prior art. It includes an outer shaft, a balloon attached to the outer shaft and adapted for inflation through the outer shaft, and a cylindrical inner tube comprised of a wound wire extending within the inner shaft, the inner tube being open at the distal end to form a lumen for a separate guidewire.

10 The wound wire is preferably made of stainless steel flat wire, and the preferred dimensions for the flat wire are 0.0015 inches by 0.006 inches. Usually the inner lumen is jacketed with a biocompatible polymer, preferably polyethylene. Sometimes a lubricious coating is applied to the interior of the inner lumen, and the outer shaft may be made of more than one material to enhance both stiffness and flexibility, while maintaining a good-sized inflation lumen.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a plan view of the entire catheter.

Fig. 2 illustrates a transition zone between the proximal and the distal portion of the outer shaft of the catheter.

25 Fig. 3 is a cross-section of the catheter taken at lines 3-3 of Fig. 2.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

SUBSTITUTE SHEET

The catheter 1 of the present invention is shown generally in Fig. 1. It includes a tubular outer shaft 2, a generally cylindrical inflatable balloon 4, and an inner tube or lumen 6. The balloon is heat shrunk at its proximal end 8 to the outer shaft, and at its distal end 10 to the inner tube, about 2 mm back from the distal tip 26 of the catheter. The balloon preferably has a 20 cm working length.

The outer shaft and inner tube define a lumen 30 therebetween shown on Fig. 3, a cross-section of the catheter. This lumen is used for inflation of the balloon and is open to the interior 12 of the balloon. A Y-shaped manifold 14 of polycarbonate is attached to the outer shaft at the proximal end, via a transition zone of strain relief tubing 26 and 28 formed of polyethylene (preferably Rexene 1017). It includes one arm 16 accessing the inflation lumen for inflation of the balloon.

The manifold has a second arm 18 which accesses the guidewire lumen 20. Guidewire lumen 20 extends the length of the catheter within the inner tube 6. It is designed so that a guidewire (32 shown in dotted lines in Fig. 3) can be slidably inserted therethrough. The distal end 26 of the inner tube 6 is open so that the guidewire can be extended through and out the distal end of the catheter.

The inner tube, i.e., the "spring inner lumen" is comprised of a helically wound coil of a biocompatible material. The wire from which the coil is wound is preferably a flat wire, which gives the inner tube advantageous characteristics. In particular, it provides a smoother surface so that a guidewire (particularly a standard one with round wire) can be easily slid through. Because of the relatively large mutually-contacting surface of adjacent coils of flat wire, axial strength and stiffness is greater than in the case of

SUBSTITUTE SHEET

round wire even while a thinner wire is used to minimize the catheter profile.

5 In the preferred embodiment, the flat wire is formed of stainless steel (metal is preferred because it does not deform as do most polymers used for tubing) with dimensions of about 0.0015 by 0.006 inches. These dimensions appear to maximize axial strength and flexibility while maintaining desired catheter dimensions. However, other sizes can be used such as those ranging from about 0.001 to 0.003 inches in thickness and about 0.004 to 0.001 inches in width.

10 The inner lumen has a heat shrunk jacket 34 formed of a low density polyethylene, such as Rexene 1017. A marker band is located at the center of the balloon, is formed of gold, and is heat shrunk into place by the polyethylene jacket. A lubricious material such as Enhance™ silicone coating may be coated on the inner surface to enhance handling of the guidewire. The entire spring coil, before it is wound or jacketed, may be coated with other materials such as Teflon™ to enhance lubricity or provide other advantages. In some 15 embodiments, the spring coil has been plated with gold.

20 When intended for use with a guidewire up to about 14K (0.014 inches) in size, the inner diameter of the inner tube is about 0.017 to 0.019 inches, and the outer diameter of the coil itself is about 0.022 inches. The overall diameter of the inner tube with jacket is about 0.024 to about 0.025 inches.

25 The outer shaft 2 is preferably formed of a biocompatible flexible material such as those known in the art for use in catheters. Particular materials can be polyimides, polyethylenes, and the like. In the preferred embodiment, two materials are used. The proximal portion 22 of the shaft; 30 usually about 105 cm long, is formed of polyethylene

terephthalate, preferably Traytuf PET #7200c, and the distal 28 cm or so of the shaft, 24, is formed of polyethylene, preferably Rexene 1017.

5 The joint 36 between the two portions of the shaft, which is about 5 mm long in the preferred embodiment, is illustrated on Fig. 2; the two portions are overlapped and joined by a biocompatible adhesive such as cyanocrylate. The dual materials are included because PET forms a stiffer shaft than the polyethylene; it provides a stiff proximal end where the catheter is pushed by the user. The polyethylene distal shaft provides more flexibility for a more easily-steerable tip; in addition, the profile of the polyethylene portion is kept smaller for ease of tracking in the coronary vessels. The inner diameter of the PET outer shaft is preferably about 15 0.034 inches, while the outer diameter is preferably about 0.042 inches. The polyethylene portion, in contrast, has an inner diameter of about 0.031 inches and an outer diameter of about 0.038 inches.

20 It will be understood that the above description and the illustrations are provided by way of example only, that alternate versions, equivalents, and examples will be apparent to those skilled in the art, and will be within the scope of the invention which is defined by the appended claims:



WHAT IS CLAIMED IS:

1. A catheter comprising:
an outer tubular shaft;
a balloon attached to the outer shaft and adapted for
inflation through the outer shaft;
a cylindrical inner tube comprised of a wound wire
extending within the inner shaft, the inner tube being open at
the distal end to form a lumen for a separate guidewire.
2. A catheter according to claim 1 and wherein the wound wire
is made of metal.
3. A catheter according to claim 2 and wherein the wound wire
is flat wire.
4. A catheter according to 3 and wherein the flat wire is
stainless steel having dimensions of about 0.0015 inches by
0.006 inches.
5. A catheter according to claim 1 and wherein the wound wire
is jacketed with a biocompatible polymer material.
6. A catheter according to claim 5 and wherein the jacket is
formed of polyethylene.
7. A catheter according to claim 2 and wherein a lubricious
coating is applied to the interior of the inner tube.
8. A catheter according to claim 1 and wherein the outer
shaft is formed of polyethylene terephthalate at its proximal
portion and polyethylene at its distal end.

SUBSTITUTE SHEET

9. A catheter according to claim 1 and wherein about the proximal three-quarters of outer shaft has a greater outer diameter than the distal portion.

SUBSTITUTE SHEET



SUBSTITUTE SHEET

2/2




FIG. 2

SUBSTITUTE SHEET

INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 92/07948

I. CLASSIFICATION OF SUBJECT MATTER (If several classification symbols apply, indicate all) ⁶		
According to International Patent Classification (IPC) or to both National Classification and IPC		
Int.Cl. 5 A61M29/02		
II. FIELDS SEARCHED		
Minimum Documentation Searched ⁷		
Classification System	Classification Symbols	
Int.Cl. 5	A61M	
Documentation Searched other than Minimum Documentation to the Extent that such Documents are Included in the Fields Searched ⁸		
III. DOCUMENTS CONSIDERED TO BE RELEVANT⁹		
Category ¹⁰	Citation of Document, ¹¹ with indication, where appropriate, of the relevant passages ¹²	Relevant to Claim No. ¹³
X	WO,A,8 901 800 (HESS) 9 March 1989 cited in the application see the whole document ---	1,2,4,8
A	WO,A,9 113 649 (MEDTRONIC) 19 September 1991 see page 2, line 30 - page 3, line 30; figure 2 ---	1-4,8
A	EP,A,0 397 459 (MEDTRONIC) 14 November 1990 see column 4, line 7 - line 33; figures 1,5,6,8 ---	1-4
A	WO,A,8 200 592 (URESIL) 4 March 1982 cited in the application see abstract; figures 1-5 ---	1,2,4
-/-		
<p>¹⁰ Special categories of cited documents:</p> <p>"A" document defining the general state of the art which is not considered to be of particular relevance</p> <p>"E" earlier document but published on or after the international filing date</p> <p>"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)</p> <p>"O" document referring to an oral disclosure, use, exhibition or other means</p> <p>"P" document published prior to the international filing date but later than the priority date claimed</p> <p>"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention</p> <p>"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step</p> <p>"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.</p> <p>"A" document member of the same patent family</p>		
IV. CERTIFICATION		
Date of the Actual Completion of the International Search	Date of Mailing of this International Search Report	
22 JANUARY 1993	01.02.93	
International Searching Authority	Signature of Authorized Officer	
EUROPEAN PATENT OFFICE	KOUSOURETAS I.	

III. DOCUMENTS CONSIDERED TO BE RELEVANT (CONTINUED FROM THE SECOND SHEET)		Relevant to Claims No.
Category *	Citation of Document, with indication, where appropriate, of the relevant passages	
A'	US,A,4 917 666 (SOLAR) 17 April 1990 see column 5, line 9 - column 7, line 7; figures 1-6	1,2,4,5, 8,9
A	EP,A,0 358 117 (ADVANCED CARDIOVASCULAR SYSTEMS) 14 March 1990 see abstract	1,7,9

**ANNEX TO THE INTERNATIONAL SEARCH REPORT
ON INTERNATIONAL PATENT APPLICATION NO.**

US 9207948
SA 64929

This annex lists the patent family members relating to the patent documents cited in the above-mentioned international search report.
The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information. 22/01/93

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO-A-8901800	09-03-89	US-A- 4808164	28-02-89
		EP-A- 0377656	18-07-90
		JP-T- 3501089	14-03-91
		US-A- 4927413	22-05-90
WO-A-9113649	19-09-91	EP-A- 0472716	04-03-92
EP-A-0397459	14-11-90	CA-A- 2016178	08-11-90
		JP-A- 3029669	07-02-91
WO-A-8200592	04-03-82	US-A- 4351341	28-09-82
		CA-A- 1170140	03-07-84
		CA-C- 1186581	07-05-85
		DE-C- 3152257	08-05-91
		EP-A,B 0057698	18-08-82
		EP-A,B 0212696	04-03-87
		GB-A,B 2092007	11-08-82
		GB-A,B 2140304	28-11-84
		GB-A,B 2140305	28-11-84
		SE-B- 448947	30-03-87
		SE-A- 8202253	07-04-82
		US-A- 4444188	24-04-84
		US-A- 4614188	30-09-86
US-A-4917666	17-04-90	DE-A- 3937531	17-05-90
		JP-A- 2172474	04-07-90
		NL-A- 8902698	01-06-90
EP-A-0358117	14-03-90	US-A- 4981478	01-01-91
		JP-A- 2191465	27-07-90

EPO FORM P007

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82